



P3 filter



Respiratory protection: filters

Description and composition:

This filter is manufactured with high-resistance materials that do not produce noxious effects to the user's health and hygiene.

It is designed to offer excellent protection against: solid and liquid particles, such as dust, smoke, aerosols...

This filter may be used with all Medop half masks with a threaded connection.

Maximum level of use:

Particle filter - Use level 3: limit value $<0.1 \text{ mg/m}^3$ (50 x TLV)

Weight: 350 g



Universal threaded connection





Protection against: particles



Category III

Ref.	Product
901.149	P3 filter

Respiratory protection: filters

Standard and certification	EN 143 CE
Applications	Asbestos removal, work with paint containing chrome, work with beech and oak wood, stainless steel, laser cutting, certain types of welding, dust spraying, power plants. Typical industrial applications for them are mining, construction, products manufactured with metal, pharmaceuticals, etc. Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way:  XX/XXXX (MONTH/YEAR)
Directions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: <ul style="list-style-type: none">- You find it hard to breathe.- You feel dizzy or vertigo.- You smell or taste contaminant.
Presentation	6 units per box. 8 boxes per carton. Measurements: 483 x 262 x 507 mm
	
Bar code	GTIN-13: 8423173098933 GTIN-14: 28423173098937

